

LANCOM 1790-4G+

Versatile connected via LTE-Advanced or external modems



This SD-WAN gateway offers you secure VPN functionality with maximum freedom of choice regarding the Internet lines available at the site: Thus, you realize reliable Internet access with additional LTE backup via the connection of any external modems. If, for example, you do not have a wired Internet connection on site, the device offers professional primary access via the LTE-Advanced cellular standard with up to 300 Mbps thanks to 4G.

- Business VPN router with LTE/4G cellular networking for up to 300 Mbps (Cat. 7)
- Gigabit Ethernet interface for connection to external DSL or cable modems
- SD-WAN – automatic VPN and VLAN configuration via the LANCOM Management Cloud
- 5 simultaneous IPSec VPN connections (25 channels optional)
- Network virtualization with up to 16 networks on one device (ARF)
- USB 2.0 port for the integration of modern IoT radio systems
- Security Made in Germany
- Maximum future compatibility, reliability, and security

LCOS 10.80

LANCOM 1790-4G+

Maximum availability

Ideal for business critical applications: The additional LTE-Advanced Modem (Cat. 7) for high-speed cellular networking with up to 300 Mbps downstream is ideal for intelligent backup scenarios or as an alternative to wired Internet connections. With an upstream rate of up to 150 Mbbps, the module offers high speed data transfer within the company network or to external cloud services.

Connects external modems

The LANCOM 1790-4G+ connects to an external modem via the Gigabit Ethernet interface, which makes you completely independent of the on-site Internet connection type.

LANCOM SD-WAN – Next-level networking

With LANCOM SD-WAN you can manage and monitor your entire corporate network centrally, cost-effectively, quickly, and stress-free! In combination with the LANCOM Management Cloud, the SD-WAN gateway gives you all the options for an automated setup of secure VPN connections (Auto-VPN) between sites, including network virtualization. Highlight features such as High Scalability VPN (HSVPN) and Advanced Mesh VPN offer you a significant plus in scalability and efficiency for a large number of branches and applications. Furthermore, if multiple WAN connections are defined, they are automatically operated in active/active mode (load balancing), thereby increasing the available total bandwidth. With Dynamic Path Selection and Dynamic Traffic Steering, applications are also dynamically routed via the best connection at any given time.

Secure communication via VPN

With virtual private networks (VPN), you use the public medium of the Internet as a communication path and secure the connection in such a way that the communication still remains completely inaccessible to external parties. This SD-WAN gateway offers you five integrated IPSec VPN channels for secure encryption, so that the protection of internal company data is always guaranteed when connecting mobile employees, home offices, or branch offices. With the LANCOM VPN Option, you can also upgrade the device to up to 25 VPN channels, so that the infrastructure can easily grow with your needs without additional hardware.

Advanced Routing & Forwarding

The LANCOM 1790-4G+ provides up to 16 securely isolated IP contexts, each of which has its own separate routing. This is an elegant way of operating IP applications with one central router and keeping the different communication channels securely separated from one another.

LCOS 10.80

LANCOM 1790-4G+

LTE modem

| | |
|--------------------------------|---|
| Supported standards | LTE, UMTS and HSPA support (mode of transmission automatically or manually adjustable), 2G/GSM is not supported |
| Supported mobile bands (3G/4G) | Band 1 (2100 MHz), Band 3 (1800 MHz), Band 7 (2600 MHz), Band 8 (900 MHz), Band 20 (800 MHz), Band 28 (700 MHz), Band 32 (1500 MHz), Band 38 (2600 MHz), Band 40 (2300 MHz), Band 41 (2500 MHz), Band 42 (2500 MHz), Band 43 (3600 MHz) |
| Maximum transmission power | +23 dBm |
| Diversity support | Receive diversity on the aux antenna (3G); MIMO (2x2) for LTE (4G) |
| Supported SIM card formats* | Mini-SIM (2FF), Micro-SIM (3FF) via adaptor, Nano-SIM (4FF) via adaptor |
| *) Note | LANCOM Systems recommends the use of a standard SIM (2FF / Mini-SIM) |

Layer 2 features

| | |
|-----------|---|
| VLAN | 4.096 IDs based on IEEE 802.1q, dynamic assignment |
| Multicast | IGMP-Snooping, MLD-Snooping |
| Protocols | Ethernet over GRE-Tunnel (EoGRE), L2TPv3, ARP-Lookup, LLDP, DHCP option 82, IPv6-Router-Advertisement-Snooping, DHCPv6-Snooping, LDRA (Lightweight DHCPv6 Relay Agent), Spanning Tree, Rapid Spanning Tree, ARP, Proxy ARP, BOOTP, DHCP, LACP |

Layer 3 features

| | |
|--------------------------------|---|
| Firewall | Stateful inspection firewall including packet filtering, extended port forwarding, N:N IP address mapping, packet tagging, support for DNS targets, user-defined rules and notifications |
| Quality of Service | Traffic shaping, bandwidth reservation, DiffServ/TOS, packet size control, layer-2-in-layer-3 tagging |
| Security | Intrusion Prevention, IP spoofing, access control lists, Denial of Service protection, detailed settings for handling reassembly, session-recovery, PING, stealth mode and AUTH port, URL blocker, password protection, programmable reset button |
| PPP authentication mechanisms | PAP, CHAP, MS-CHAP, and MS-CHAPv2 |
| High availability / redundancy | VRRP (Virtual Router Redundancy Protocol), analog/GSM modem backup |
| Router | IPv4-, IPv6-, NetBIOS/IP multiprotokoll router, IPv4/IPv6 dual stack |
| SD-WAN Application Routing | SD-WAN Application Routing in connection with the LANCOM Management Cloud |
| SD-WAN dynamic path selection | SD-WAN dynamic path selection in connection with the LANCOM Management Cloud |
| SD-WAN Zero Touch Deployment | Zero touch commissioning of the device in conjunction with the LANCOM Management Cloud |
| Router virtualization | ARF (Advanced Routing and Forwarding) up to separate processing of 16 contexts |

LCOS 10.80

LANCOM 1790-4G+

Layer 3 features

| | |
|---------------------------------|---|
| IPv4 services | HTTP and HTTPS server for configuration by web interface, DNS client, DNS server, DNS relay, DNS proxy, dynamic DNS client, DHCP client, DHCP relay and DHCP server including autodetection, NetBIOS/IP proxy, NTP client, SNTP server, policy-based routing, Bonjour-Proxy, RADIUS |
| IPv6 services | HTTP and HTTPS server for configuration by web interface, DHCPv6 client, DHCPv6 server, DHCPv6 relay, DNS client, DNS server, dynamic DNS client, NTP client, SNTP server, Bonjour-Proxy, RADIUS |
| Dynamic routing protocols | RIPv2, BGPv4, OSPFv2, LISP (Locator/ID Separation Protocol) |
| IPv4 protocols | DNS, HTTP, HTTPS, ICMP, NTP/SNTP, NetBIOS, PPPoE (server), RADIUS, RADSEC (secure RADIUS), RTP, SNMPv1,v2c,v3, TFTP, TACACS+, IGMPv3 |
| IPv6 protocols | NDP, stateless address autoconfiguration (SLAAC), stateful address autoconfiguration (DHCPv6), router advertisements, ICMPv6, DHCPv6, DNS, HTTP, HTTPS, PPPoE, RADIUS, SMTP, NTP, BGP, LISP, Syslog, SNMPv1,v2c,v3, MLDv2, PIM, NPTv6 (NAT66) |
| Multicast Routing | PIM (Protocol Independent Multicast), IGMP proxy, MLD proxy |
| WAN operating mode | VDSL, ADSL1, ADSL2 or ADSL2+ additional with external DSL modem at an ETH port, UMTS/LTE |
| WAN protocols | PPPoE, Multi-PPPoE, ML-PPP, GRE, EoGRE, PPTP (PAC or PNS), L2TPv2 (LAC or LNS), L2TPv3 with Ethernet-Pseudowire and IPoE (using DHCP or no DHCP), RIP-1, RIP-2, VLAN, IPv6 over PPP (IPv6 and IPv4/IPv6 dual stack session), IP(v6)oE (autokonfiguration, DHCPv6 or static) |
| Tunneling protocols (IPv4/IPv6) | 6to4, 6in4, 6rd (static and over DHCP), Dual Stack Lite (IPv4-in-IPv6-Tunnel), 464XLAT |

Security

| | |
|------------------------------|--|
| Intrusion Prevention | Monitoring and blocking of login attempts and port scans |
| IP spoofing | Source IP address check on all interfaces: only IP addresses belonging to the defined IP networks are allowed |
| Access control lists | Filtering of IP or MAC addresses and preset protocols for configuration access |
| Denial of Service protection | Protection from fragmentation errors and SYN flooding |
| General | Detailed settings for handling reassembly, PING, stealth mode and AUTH port |
| URL blocker | Filtering of unwanted URLs based on DNS hitlists and wildcard filters. Extended functionality with Content Filter Option |
| Password protection | Password-protected configuration access can be set for each interface |
| Alerts | Alerts via e-mail, SNMP traps and SYSLOG |
| Authentication mechanisms | PAP, CHAP, MS-CHAP and MS-CHAPv2 as PPP authentication mechanism |
| Adjustable reset button | Adjustable reset button for 'ignore', 'boot-only' and 'reset-or-boot' |

LCOS 10.80

LANCOM 1790-4G+

High availability / redundancy

| | |
|-------------------------|---|
| VRRP | VRRP (Virtual Router Redundancy Protocol) for backup in case of failure of a device or remote station. |
| FirmSafe | For completely safe software upgrades thanks to two stored firmware versions, incl. test mode for firmware updates |
| Analog/GSM modem backup | Optional operation of an analog or GSM modem at the serial interface |
| Load balancing | Static and dynamic load balancing over up to 3 WAN connections. Channel bundling with Multilink PPP (if supported by network operator) |
| VPN redundancy | Backup of VPN connections across different hierarchy levels, e.g. in case of failure of a central VPN concentrator and re-routing to multiple distributed remote sites. Any number of VPN remote sites can be defined (the tunnel limit applies only to active connections). Up to 32 alternative remote stations, each with its own routing tag, can be defined per VPN connection. Automatic selection may be sequential, or dependant on the last connection, or random (VPN load balancing) |
| Line monitoring | Line monitoring with LCP echo monitoring, dead-peer detection and up to 4 addresses for end-to-end monitoring with ICMP polling |

VPN

| | |
|------------------------------|---|
| IPSec over HTTPS | Enables IPSec VPN based on TCP (at port 443 like HTTPS) which can go through firewalls in networks where e. g. port 500 for IKE is blocked. Suitable for client-to-site connections and site-to-site connections. IPSec over HTTPS is based on the NCP VPN Path Finder technology |
| Number of VPN tunnels | Max. number of concurrent active IPSec, PPTP (MPPE) and L2TPv2 tunnels: 5 (25 with VPN 25 Option). Unlimited configurable connections. Configuration of all remote sites via one configuration entry when using the RAS user template or Proadaptive VPN. |
| Hardware accelerator | Integrated hardware accelerator for 3DES/AES encryption and decryption |
| Realtime clock | Integrated, buffered realtime clock to save the date and time during power failure. Assures timely validation of certificates in any case |
| Random number generator | Generates real random numbers in hardware, e. g. for improved key generation for certificates immediately after switching-on |
| 1-Click-VPN Client assistant | One click function in LANconfig to create VPN client connections, incl. automatic profile creation for the LANCOM Advanced VPN Client |
| 1-Click-VPN Site-to-Site | Creation of VPN connections between LANCOM routers via drag and drop in LANconfig |
| IKE, IKEv2 | IPSec key exchange with Preshared Key or certificate (RSA signature, ECDSA-Signature, digital signature) |
| Smart Certificate* | Convenient generation of digital X.509 certificates via an own certification authority (SCEP-CA) on the webpage or via SCEP. |
| Certificates | X.509 digital multi-level certificate support, compatible with Microsoft Server / Enterprise Server and OpenSSL. Secure Key Storage protects a private key (PKCS#12) from theft. |
| Certificate rollout | Automatic creation, rollout and renewal of certificates via SCEP (Simple Certificate Enrollment Protocol) per certificate hierarchy |

LCOS 10.80

LANCOM 1790-4G+

VPN

| | |
|------------------------------------|---|
| Certificate revocation lists (CRL) | CRL retrieval via HTTP per certificate hierarchy |
| OCSP Client | Check X.509 certifications by using OCSP (Online Certificate Status Protocol) in real time as an alternative to CRLs |
| OCSP Server/Responder* | Offers validity information for certificates created with Smart Certificate via OCSP |
| XAUTH | XAUTH client for registering LANCOM routers and access points at XAUTH servers incl. IKE-config mode. XAUTH server enables clients to register via XAUTH at LANCOM routers. Connection of the XAUTH server to RADIUS servers provides the central authentication of VPN-access with user name and password. Authentication of VPN-client access via XAUTH and RADIUS connection additionally by OTP token |
| RAS user template | Configuration of all VPN client connections in IKE ConfigMode via a single configuration entry |
| Proadaptive VPN | Automated configuration and dynamic creation of all necessary VPN and routing entries based on a default entry for site-to-site connections. |
| Algorithms | 3DES (168 bit), AES-CBC and -GCM (128, 192 or 256 bit), Blowfish (128 bit), RSA (1024-4096 bit), ECDSA (P-256-, P-384-, P-521-curves), Chacha20-Poly 1305 and CAST (128 bit). OpenSSL implementation with FIPS-140 certified algorithms. MD-5, SHA-1, SHA-256, SHA-384 or SHA-512 hashes |
| NAT-Traversal | NAT-Traversal (NAT-T) support for VPN over routes without VPN passthrough |
| LANCOM Dynamic VPN | Enables VPN connections from or to dynamic IP addresses. The IP address is communicated via the ICMP or UDP protocol in encrypted form. Dynamic dial-in for remote sites via connection template |
| Dynamic DNS | Enables the registration of IP addresses with a Dynamic DNS provider in the case that fixed IP addresses are not used for the VPN connection |
| Specific DNS forwarding | DNS forwarding according to DNS domain, e.g. internal names are translated by proprietary DNS servers in the VPN. External names are translated by Internet DNS servers |
| Split DNS | Allows the selective forwarding of traffic for IKEv2 depending on the addressed DNS domain. |
| IPv4 VPN | Connecting private IPv4 networks |
| IPv4 VPN over IPv6 WAN | Use of IPv4 VPN over IPv6 WAN connections |
| IPv6 VPN | Connecting private IPv6 networks |
| IPv6 VPN over IPv4 WAN | Use of IPv6 VPN over IPv4 WAN connections |
| Radius | RADIUS authorization and accounting, outsourcing of VPN configurations in external RADIUS server in IKEv2, RADIUS CoA (Change of Authorization) |
| High Scalability VPN (HSVPN) | Transmission of multiple, securely separated networks within a VPN tunnel |
| Advanced Mesh VPN | On demand dynamic VPN tunnel establishment between branches |
| IKEv2-EAP* | VPN clients can be authenticated with IKEv2-EAP against a central database like Microsoft Windows Server or RADIUS Server |

LCOS 10.80

LANCOM 1790-4G+

VPN

Two-factor authentication* Two-factor authentication with LANCOM Advanced VPN Client via IKEv2 EAP-OTP

*) Only with VPN 25 option

Performance

Routing-Performance Data regarding the overall routing performance can be found inside the LANCOM tech paper "Routing-Performance" on www.lancom-systems.com

VoIP

SIP ALG The SIP ALG (Application Layer Gateway) acts as a proxy for SIP communication. For SIP calls the ALG opens the necessary ports for the corresponding media packets. Automatic address translation (STUN is no longer needed).

Interfaces

WAN: Ethernet 10/100/1000 Mbps Gigabit Ethernet

WAN: LTE/UMTS LTE advanced, LTE, UMTS or HSxPA with integrated LTE advanced modem

Ethernet ports 3 individual 10/100/1000 Mbps Ethernet ports; up to 3 ports can be operated as additional WAN ports with load balancing. Ethernet ports can be electrically disabled within LCOS configuration. The ports support energy saving according to IEEE 802.3az

Port configuration Each Ethernet port can be freely configured (LAN, DMZ, WAN, monitor port, off). LAN ports can be operated as a switch or separately. Additionally, external DSL modems or termination routers can be operated as a WAN port with load balancing and policy-based routing. DMZ ports can be operated with their own IP address range without NAT

USB 2.0 host port USB 2.0 hi-speed host port for connecting USB printers (USB print server), serial devices (COM port server), USB data storage (FAT file system); bi-directional data exchange is possible

Serial interface Serial configuration interface / COM port (8 pin Mini-DIN): 9,600 - 115,000 baud, suitable for optional connection of analog/GPRS modems. Supports internal COM port server and allows for transparent asynchronous transmission of serial data via TCP

External antenna connectors Two SMA antenna connectors for external LTE antennas (Ant 1, Ant 2)

Management and monitoring

Management LANCOM Management Cloud, LANconfig, WEBconfig, WLAN controller, LANCOM Layer 2 management (emergency management)

Management functions Alternative boot configuration, voluntary automatic updates for LCMS and LCOS, individual access and function rights up to 16 administrators, RADIUS and RADSEC user management, remote access (WAN or (W)LAN, access rights (read/write) adjustable separately), SSL, SSH, HTTPS, Telnet, TFTP, SNMP, HTTP, access rights via TACACS+, scripting, timed control of all parameters and actions through cron job

FirmSafe Two stored firmware versions, incl. test mode for firmware updates

automatic firmware update configurable automatic checking and installation of firmware updates

LCOS 10.80

LANCOM 1790-4G+

Management and monitoring

| | |
|-----------------------|---|
| Monitoring | LANCOM Management Cloud, LANmonitor, WLANmonitor |
| Monitoring functions | Device SYSLOG, SNMPv1,v2c,v3 incl. SNMP-TRAPS, extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, internal logging buffer for firewall events |
| Monitoring statistics | Extensive Ethernet, IP and DNS statistics; SYSLOG error counter, accounting information exportable via LANmonitor and SYSLOG |
| IPerf | IPerf is a tool for measurements of the bandwidth on IP networks (integrated client and server) |
| SLA-Monitor (ICMP) | Performance monitoring of connections |
| Netflow | Export of information about incoming and outgoing IP traffic |
| SD-LAN | SD-LAN – automatic LAN configuration via the LANCOM Management Cloud |
| SD-WAN | SD-WAN – automatic WAN configuration via the LANCOM Management Cloud |

Hardware

| | |
|-------------------------|--|
| Weight | 1,05 lbs (478 g) |
| Environment | Temperature range 0–40°C; humidity 0–95%; non-condensing |
| Housing | Robust synthetic housing, rear connectors, ready for wall mounting, Kensington lock; 210 x 45 x 140 mm (W x H x D) |
| Fans | 1 silent fan |
| Power consumption (max) | 9 watt |

Declarations of conformity*

| | |
|-------------------|---|
| Europe/EFTA | CE |
| IPv6 | IPv6 Ready Gold |
| Country of Origin | Made in Germany |
| *) Note | You will find all declarations of conformity on our website at www.lancom-systems.com/doc |

Scope of delivery

| | |
|----------|--|
| Manual | Hardware Quick Reference (DE/EN), Installation Guide (DE/EN) |
| Cable | 1 Ethernet cable, 3 m |
| Antennas | Two 2 dBi LTE/UMTS-antennas |

LCOS 10.80

lancom-systems.com

LANCOM 1790-4G+

Scope of delivery

| | |
|-------------------|--|
| Power supply unit | External power adapter (230 V), NEST 12 V/2.0 A DC/S, coaxial power connector 2.1/5.5 mm, temperature range from -5 to +45° C, LANCOM item no. 111303 (EU) |
|-------------------|--|

Support

| | |
|--------------------------------|--|
| Warranty | 3 years For details, please refer to the General Warranty Conditions at: www.lancom-systems.com/warranty-conditions |
| Security updates | 3 years, can be extended by purchasing LANcare products |
| Software updates | Regular free updates as part of the LANCOM Lifecycle Managements (www.lancom-systems.com/lifecycle) |
| Manufacturer support | Technical manufacturer support as part of a support contract (LANcommunity partner, LANcare Direct, or LANcare Premium Support) |
| LANcare Basic S | Security updates and manufacturer support until EOL status (min. 5 years, support contract required: LANcommunity partner, LANcare Direct, or LANcare Premium Support), 5 years replacement service with shipment of the device within 5 days after arrival of the faulty device (8/5/5Days), 10720 |
| LANcare Advanced S | Security updates and manufacturer support until EOL status (min. 5 years, support contract required: LANcommunity partner, LANcare Direct, or LANcare Premium Support), 5 years NBD advance replacement with delivery of the device on the next business day (8/5/NBD), item no. 10730 |
| LANcare Direct Advanced 24/7 S | Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, NBD advance replacement with delivery of the device on the next business day (24/7/NBD), guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10776, 10777 or 10778) |
| LANcare Direct 24/7 S | Direct, prioritized 10/5 manufacturer support incl. 24/7 emergency hotline and security updates for the device, guaranteed first response times (SLA) of max. 30 minutes for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years (item no. 10752, 10753 or 10754) |
| LANcare Direct Advanced 10/5 S | Direct, prioritized 10/5 manufacturer support and security updates for the device, NBD advance replacement with delivery of the device on the next business day (10/5/NBD), guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years.(item no. 10764, 10765 or 10766) |
| LANcare Direct 10/5 S | Direct, prioritized 10/5 manufacturer support and security updates for the device, guaranteed first response times (SLA) of max. 2 hours for reporting massive operational disruptions by telephone (priority 1) and max. 4 hours for all other concerns (priority 2), term-based for 1, 3, or 5 years.(item no. 10740, 10741 or 10742) |

Software

| | |
|----------------------|--|
| Lifecycle Management | After discontinuation (End of Sale), the device is subject to the LANCOM Lifecycle Management. Details can be found at: www.lancom-systems.com/lifecycle |
| Anti-backdoor policy | Products from LANCOM are free of hidden access paths (backdoors) and other undesirable features for introducing, extracting or manipulating data. The trust seal "IT Security made in Germany" (ITSMIG) and certification by the German Federal Office for Information Security (BSI) confirm the trustworthiness and the outstanding level of security. |

LCOS 10.80

LANCOM 1790-4G+

Options

| | |
|--|--|
| VPN | LANCOM VPN-25 Option (25 channels), item no. 60083 |
| LANCOM Content Filter | LANCOM Content Filter +10 user (additive up to 100), 1 year subscription, item no. 61590 |
| LANCOM Content Filter | LANCOM Content Filter +25 user (additive up to 100), 1 year subscription, item no. 61591 |
| LANCOM Content Filter | LANCOM Content Filter +100 user (additive up to 100), 1 year subscription, item no. 61592 |
| LANCOM Content Filter | LANCOM Content Filter +10 user (additive up to 100), 3 year subscription, item no. 61593 |
| LANCOM Content Filter | LANCOM Content Filter +25 user (additive up to 100), 3 year subscription, item no. 61594 |
| LANCOM Content Filter | LANCOM Content Filter +100 user (additive up to 100), 3 year subscription, item no. 61595 |
| LANCOM BPjM Filter | LANCOM BPjM Filter Option, 5 years subscription, item no. 61418 |
| LANCOM Public Spot | Hotspot option for LANCOM products, versatile access (via voucher, e-mail, SMS), including a comfortable setup wizard, secure separation of guest access and internal network, item no. 60642 |
| LANCOM All-IP Lizenz Option | Upgrade option for the operation of the LANCOM routers with All-IP connections, support of PBX systems and telephony devices as well as voice & fax services, incl. Voice Call Manager, item no. 61419 |
| LANCOM Public Spot PMS Accounting Plus | Extension of the LANCOM Public Spot (XL) Option for the connection to hotel billing systems with FIAS interface (such as Micros Fidelio) for authentication and billing of guest accesses for 178x/19xx routers, WLCs, and current central-site gateways, item no. 61638 |
| LANCOM WLC Basic Option for Routers | LANCOM WLC Basic Option for Routers for up to 6 managed LANCOM access points or WLAN routers, item no. 61639 |
| LANCOM VoIP +10 Option | Upgrade for LANCOM VoIP router with 10 additional internal VoIP numbers (additionally up to 40) and 10 external SIP lines (additionally up to 55) item no. 61423 |

LANCOM Management Cloud

| | |
|-----------------------------|--|
| LANCOM LMC-B-1Y LMC License | LANCOM LMC-B-1Y License (1 Year), enables the management of one category B device for one year via the LANCOM Management Cloud, item no. 50103 |
| LANCOM LMC-B-3Y LMC License | LANCOM LMC-B-3Y License (3 Years), enables the management of one category B device for three years via the LANCOM Management Cloud, item no. 50104 |
| LANCOM LMC-B-5Y LMC License | LANCOM LMC-B-5Y License (5 Years), enables the management of one category B device for five years via the LANCOM Management Cloud, item no. 50105 |

Accessories

| | |
|------------------|---|
| External antenna | AirLancer I-360D-5G, omnidirectional outdoor antenna MIMO (2x2), for all 4G/5G bands (698-3800 MHz), item no. 60919 |
| External antenna | AirLancer O-360D-5G, omnidirectional outdoor antenna MIMO (2x2), for all 4G/5G bands (698-3800 MHz), item no. 61233 |

LCOS 10.80

LANCOM 1790-4G+

Accessories

| | |
|----------------------------|---|
| 19" Rack Mount | 19" rack mount adaptor, item no. 61501 |
| 19" Rack Mount | 19" rack mount plus adaptor, item no. 61644 |
| LANCOM Wall Mount | For simple, theft-proof mounting of LANCOM devices with plastic housings, item no. 61349 |
| LANCOM Wall Mount (White) | For simple, theft-proof mounting of LANCOM devices with plastic housings, item no. 61345 |
| LANCOM Serial Adapter Kit | For the connection of V.24 modems with AT command set and serial interface for the connection to the LANCOM COM interface, incl. serial cable and connection plug, item no. 61500 |
| LANCOM Wireless ePaper USB | Update of LANCOM Wireless ePaper Displays in the 2.4 GHz frequency band, item no. 62225 |
| VPN Client Software | LANCOM Advanced VPN Client for Windows 7,8/8.1,10,11 - single license, item no. 61600 |
| VPN Client Software | LANCOM Advanced VPN Client for Windows 7,8/8.1,10,11 - 10 licenses, item no. 61601 |
| VPN Client Software | LANCOM Advanced VPN Client for Windows 7,8/8.1,10,11 - 25 licenses, item no. 61602 |
| VPN Client Software | LANCOM Advanced VPN Client for Mac OS X (10.5 Intel only, 10.6 or higher), single license, item no. 61606 |
| VPN Client Software | LANCOM Advanced VPN Client for Mac OS X (10.5 Intel only, 10.6 or higher), 10 licenses, item no. 61607 |

Item number(s)

| | |
|----------------------|-------|
| LANCOM 1790-4G+ (EU) | 62135 |
|----------------------|-------|

