

## LANCOM 1781AW

**Business VPN router with integrated ADSL2+ modem and WLAN with up to 300 Mbps for secure site connectivity**



The LANCOM 1781AW is a professional, high-performance VPN router with integrated ADSL2+ modem and Wi-Fi based on IEEE 802.11n. Thanks to a wide range of VPN capabilities, the LANCOM 1781AW helps businesses, branch offices and retail stores to network their different sites with maximum security, while supporting a Wi-Fi network at the same time. The right choice for secure, reliable, and sustainable networking solutions "Made in Germany".

- Business VPN router with an integrated ADSL2+ modem and Wi-Fi based on IEEE 802.11n for up to 300 Mbps
- Secure site connectivity with 5 simultaneous IPsec VPN connections (25 channels optional)
- Integrated stateful-inspection firewall with intrusion detection and Denial-of-Service protection
- Network virtualization with up to 16 networks on one device (ARF)
- Security Made in Germany
- Maximum future compatibility, reliability, and security

LCOS 10.50

# LANCOM 1781AW

## **Business VPN router with ADSL2+ modem**

With its integrated ADSL2+ modem, the LANCOM 1781AW connects to a normal ADSL connection to provide professional Internet access for businesses, offices and retail stores.

## **Wi-Fi based on IEEE 802.11n**

Featuring IEEE 802.11n Wi-Fi, the LANCOM 1781AW provides wireless networking to clients in the 2.4- or 5-GHz frequency range at speeds of up to 300 Mbps. Secure wireless LAN with the LANCOM 1781AW is assured by its wide range of supported security standards including IEEE 802.1i (WPA2) and IEEE 802.1X. Thanks to multi-SSID, the wireless LAN also supports multiple networks that are securely separated from one another.

## **Secure site connectivity via VPN**

The LANCOM 1781AW offers high levels of security. The standard equipment of 5 IPSec VPN channels guarantees strong encryption, secure connections for mobile employees, and protection of corporate data. The LANCOM VPN option upgrades the router to support 25 VPN channels. This ensures that your network is perfectly scalable and can grow on demand—without additional hardware components.

## **Stateful inspection firewall**

Equipped with a stateful inspection firewall, the LANCOM 1781AW protects the entire network. With features such as intrusion prevention and Denial-of-Service protection, this business VPN router provides optimal protection and secures all of the data on the network.

## **Advanced Routing & Forwarding**

The LANCOM 1781AW provides up to 16 securely isolated IP contexts, each of which has its own separate routing. This is an elegant way of operating IP applications with one central router and keeping the different communication channels securely separated from one another.

LCOS 10.50

# LANCOM 1781AW

## WLAN product specifications

Frequency band 2.4 GHz or 5 GHz	2400-2483.5 MHz (ISM) or 5150-5825 MHz (depending on country-specific restrictions)
Data rates IEEE 802.11n	300 Mbps according to IEEE 802.11n with MCS15 (fallback to 6,5 Mbps with MCS0). Compatible to IEEE 802.11a/n, IEEE 802.11g/n, IEEE 802.11b/g/n or IEEE 802.11b/g compatibility mode or pure IEEE 802.11n, pure IEEE 802.11a, IEEE 802.11g or pure IEEE 802.11b mode and data rates selectable
Data rates IEEE 802.11a/ h	54 Mbps (fallback to 48, 36 , 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection), fully compatible with TPC (adjustable power output) and DFS (automatic channel selection, radar detection) and data rates selectable
Data rates IEEE 802.11b/g	54 Mbps to IEEE 802.11g (fallback to 48, 36, 24, 18, 12, 9, 6 Mbps, Automatic Rate Selection) compatible to IEEE 802.11b (11, 5.5, 2, 1 Mbps, Automatic Rate Selection), IEEE 802.11b/g compatibility mode or pure IEEE 802.11g or pure IEEE 802.11b and data rates selectable
Range IEEE 802.11a/b/g *	Up to 150 m (up to 30 m in buildings)
Output power at radio module, 5 GHz	IEEE 802.11a/h: +15 dBm @ 6 up to 36 Mbps, +14 dBm @ 48 Mbps, +12 dBm @ 54 Mbps IEEE 802.11n: +15 dBm @ (MCS0/8, 20 MHz), +7 up to +10 dBm @ (MCS7/15, 20 MHz), +14 dBm @ (MCS0/8, 40 MHz), +6 up to +9 dBm @ (MCS7/15, 40 MHz)
Output power at radio module, 2.4 GHz	IEEE 802.11b: +14dBm @ 1, 2, 5.5 and 11 Mbps, IEEE 802.11g: +17dBm @ 6 up to 36 Mbps, +16dBm @ 48 and 54 Mbps, IEEE 802.11n: +16dBm @ (MCS0/8, 20 MHz), +15 dBm @ (MCS7/15, 20 MHz), +15 dBm @ (MCS0/8, 40 MHz), +14 dBm @ (MCS7/15, 40 MHz)
Max. allowed radiation power (EIRP), 5 GHz	IEEE 802.11a/h: Up to 30 dBm / 1000 mW EIRP (depending on national regulations on channel usage and subject to further obligations such as TPC and DFS)
Max. allowed radiation power (EIRP), 2.4 GHz	IEEE 802.11b/g: Up to 20 dBm / 100 mW EIRP (transmission power control according to TPC)
Minimum transmission power	Transmission power reduction in software in 1 dB steps to min. 0.5 dBm
Receiver sensitivity 5 GHz	IEEE 802.11a/h: -98 dBm @ 6 Mbps, -81 dBm @ 54 Mbps, IEEE 802.11n: -94 dBm @ (MCS0, 20 MHz), -76dBm @ (MCS 7, 20 MHz), -92 dBm @ (MCS0, 40 MHz), -72 dBm @ (MCS7, 40 MHz)
Receiver sensitivity 2.4 GHz	IEEE 802.11b: -97 dBm @ 1 MBit/s, -93 dBm @ 11 MBit/s, IEEE 802.11g: -95dBm @ 6 MBit/s, -81dBm @ 54 MBit/s IEEE 802.11n: -94 dBm @ 6,5MBit/s (MCS0, 20 MHz), -77 dBm @ 65 MBit/s (MCS7, 20 MHz), -91 dBm @ 15 MBit/s (MCS0, 40 MHz), -74 dBm @ 150 MBit/s (MCS7, 40 MHz)
Radio channels 5 GHz	Up to 26 non-overlapping channels (available channels and further obligations such as automatic DFS dynamic channel selection depending on national regulations)
Radio channels 2.4 GHz	Up to 13 channels, max. 3 non-overlapping (depending on country-specific restrictions)
Multi-SSID	Up to 16 independent WLAN networks; time-controlled activation and deactivation of WLAN networks
Concurrent WLAN clients	Up to 40 clients (recommended), 512 clients (max.)
*) Note	The effective distances and transmission rates that can be achieved are depending of the onsite RF conditions

LCOS 10.50

# LANCOM 1781AW

## Supported WLAN standards

IEEE standards	IEEE 802.11n (Wi-Fi 4), IEEE 802.11a, IEEE 802.11g, IEEE 802.11b, IEEE 802.11i, IEEE 802.1X, IEEE 802.11u, IEEE 802.11r (Fast Roaming), IEEE 802.11w (Protected Management Frames), WME and U-APSD/WMM Power Save as defined in IEEE 802.11e, IEEE 802.11h, IEEE 802.11d
----------------	--

## Standard IEEE 802.11n (Wi-Fi 4)

Supported features	2x2 MIMO, 40 MHz channel, 20/40MHz coexistence mechanisms in the 2.4 GHz band, MAC aggregation, Block Acknowledgement, STBC (Space Time Block Coding), LDPC (Low Density Parity Check), MRC (Maximal Ratio Combining), Short Guard Interval
--------------------	---

## WLAN operating modes

Modes	WLAN access point (standalone, WLC or LANCOM Management Cloud managed), WLAN bridge (P2P or P2MP) (standalone or AutoWDS*), (standalone, WLC or LANCOM Management Cloud managed), WLAN client mode, transparent WLAN client mode
-------	--

\*) Note Only in installations with WLAN controller

## Security

Encryption options	WPA3-Personal, IEEE 802.1X (WPA3-Enterprise, WPA2-Enterprise), IEEE 802.11i (WPA2-Personal), Wi-Fi Certified™ WPA2™, WPA, WEP, IEEE 802.11w (Protected Management Frames), LEPS-MAC (LANCOM Enhanced Passphrase Security MAC), LEPS-U (LANCOM Enhanced Passphrase Security User)
--------------------	--

Encryption AES-CCMP AES-GCMP, TKIP, RC4 (only used by WEP)

EAP types (authenticator) EAP-TLS, EAP-TTLS/MSCHAPv2, PEAPv0/EAP-MSCHAPv2, PEAPv1/EAP-GTC, EAP-FAST

RADIUS/EAP-server User administration MAC-based, rate limiting, passphrases, VLAN user based, authentication of IEEE 802.1X clients via EAP-TLS, EAP-TTLS, EAP-MD5, EAP-GTC, PEAP, MSCHAP, MSCHAPv2, Dynamic Peer Discovery

Others WLAN protocol filters, IP-redirection of any packet received over the WLAN interface, IEEE 802.1X supplicant, background scanning, client detection ("rogue WLAN client detection"), Wireless Intrusion Detection System (WIDS), RADIUS CoA (Change of Authorization)

## LANCOM Active Radio Control

Client Management Steering of WLAN clients to the ideal access point using 802.11k and 802.11v

Managed RF Optimization\* Selection of optimal WLAN channels by the administrator

Adaptive Noise Immunity Better WLAN throughput due to immunity against interferences

Spectral Scan Monitoring your WLAN for sources of interference

Adaptive RF Optimization Dynamic selection of the optimal WLAN channel

Airtime Fairness Improved utilization of the WLAN bandwidth

Adaptive Transmission Power Automatic adjustment of the transmission power for Wi - Fi backup scenarios

LCOS 10.50

# LANCOM 1781AW

## LANCOM Active Radio Control

\*) Note Only in installations with WLAN controller

## Roaming

Roaming IAPP (Inter Access Point Protocol), IEEE 802.11r (Fast Roaming), OKC (Opportunistic Key Caching), Fast Client Roaming (only in operating mode client modus)

## Layer 2 features

VLAN 4.096 IDs based on IEEE 802.1q, dynamic assignment

Quality of Service WME based on IEEE 802.11e, Wi-Fi Certified™ WMM®

Rate limiting SSID based, WLAN client based

Multicast IGMP-Snooping, MLD-Snooping, Multicast-to-Unicast-conversion on WLAN interfaces

Protocols Ethernet over GRE-Tunnel (EoGRE), L2TPv3, ARP-Lookup, LLDP, DHCP option 82, IPv6-Router-Advertisement-Snooping, DHCPv6-Snooping, LDRA (Lightweight DHCPv6 Relay Agent), Spanning Tree, Rapid Spanning Tree, ARP, Proxy ARP, BOOTP, DHCP, LACP

## Layer 3 features

Firewall Stateful inspection firewall including packet filtering, extended port forwarding, N:N IP address mapping, packet tagging, support for DNS targets, user-defined rules and notifications

Quality of Service Traffic shaping, bandwidth reservation, DiffServ/TOS, packet size control, layer-2-in-layer-3 tagging

Security Intrusion Prevention, IP spoofing, access control lists, Denial of Service protection, detailed settings for handling reassembly, session-recovery, PING, stealth mode and AUTH port, URL blocker, password protection, programmable reset button

PPP authentication mechanisms PAP, CHAP, MS-CHAP, and MS-CHAPv2

High availability / redundancy VRRP (Virtual Router Redundancy Protocol), analog/GSM modem backup

Router virtualization ARF (Advanced Routing and Forwarding) up to separate processing of 16 contexts

IPv4 services HTTP and HTTPS server for configuration by web interface, DNS client, DNS server, DNS relay, DNS proxy, dynamic DNS client, DHCP client, DHCP relay and DHCP server including autodetection, NetBIOS/IP proxy, NTP client, SNTP server, policy-based routing, Bonjour-Proxy, RADIUS

IPv6 services HTTP and HTTPS server for configuration by web interface, DHCPv6 client, DHCPv6 server, DHCPv6 relay, DNS client, DNS server, dynamic DNS client, NTP client, SNTP server, Bonjour-Proxy, RADIUS

Dynamic routing protocols RIPv2, BGPv4, OSPFv2, LISP (Locator/ID Separation Protocol)

IPv4 protocols DNS, HTTP, HTTPS, ICMP, NTP/SNTP, NetBIOS, PPPoE (server), RADIUS, RADSEC (secure RADIUS), RTP, SNMPv1,v2c,v3, TFTP, TACACS+, IGMPv3

LCOS 10.50

# LANCOM 1781AW

## Layer 3 features

IPv6 protocols	NDP, stateless address autoconfiguration (SLAAC), stateful address autoconfiguration (DHCPv6), router advertisements, ICMPv6, DHCPv6, DNS, HTTP, HTTPS, PPPoE, RADIUS, SMTP, NTP, BGP, LISP, Syslog, SNMPv1,v2c,v3, MLDv2, PIM, NPTv6 (NAT66)
Multicast Routing	PIM (Protocol Independent Multicast), IGMP proxy, MLD proxy
WAN operating mode	VDSL, ADSL1, ADSL2 or ADSL2+ additional with external DSL modem at an ETH port
WAN protocols	PPPoE, Multi-PPPoE, ML-PPP, GRE, EoGRE, PPTP (PAC or PNS), L2TPv2 (LAC or LNS), L2TPv3 with Ethernet-Pseudowire, IPoE (using DHCP or no DHCP), RIP-1, RIP-2, VLAN, IPv6 over PPP (IPv6 and IPv4/IPv6 dual stack session), IP(v6)oE (autokonfiguration, DHCPv6 or static)
Tunneling protocols (IPv4/IPv6)	6to4, 6in4, 6rd (static and over DHCP), Dual Stack Lite (IPv4-in-IPv6-Tunnel), 464XLAT

## Security

Intrusion Prevention	Monitoring and blocking of login attempts and port scans
IP spoofing	Source IP address check on all interfaces: only IP addresses belonging to the defined IP networks are allowed
Access control lists	Filtering of IP or MAC addresses and preset protocols for configuration access and LANCAPI
Denial of Service protection	Protection from fragmentation errors and SYN flooding
General	Detailed settings for handling reassembly, PING, stealth mode and AUTH port
Password protection	Password-protected configuration access can be set for each interface
Alerts	Alerts via e-mail, SNMP traps and SYSLOG
Authentication mechanisms	EAP-TLS, EAP-TTLS, PEAP, MS-CHAP, MS-CHAPv2 as EAP authentication mechanisms, PAP, CHAP, MS-CHAP and MS-CHAPv2 as PPP authentication mechanisms
Anti-theft	Anti-theft ISDN site verification over B or D channel (self-initiated call back and blocking)
WLAN protocol filters	Limitation of the allowed transfer protocols, source and target addresses on the WLAN interface
Adjustable reset button	Adjustable reset button for 'ignore', 'boot-only' and 'reset-or-boot'
IP redirect	Fixed redirection of any packet received over the WLAN interface to a dedicated target address

## High availability / redundancy

VRRP	VRRP (Virtual Router Redundancy Protocol) for backup in case of failure of a device or remote station.
FirmSafe	For completely safe software upgrades thanks to two stored firmware versions, incl. test mode for firmware updates
ISDN backup	In case of failure of the main connection, a backup connection is established over ISDN. Automatic return to the main connection

LCOS 10.50

# LANCOM 1781AW

## High availability / redundancy

Analog/GSM modem backup	Optional operation of an analog or GSM modem at the serial interface
Load balancing	Static and dynamic load balancing over up to 4 WAN connections (incl. client binding). Channel bundling with Multilink PPP (if supported by network operator)
VPN redundancy	Backup of VPN connections across different hierarchy levels, e.g. in case of failure of a central VPN concentrator and re-routing to multiple distributed remote sites. Any number of VPN remote sites can be defined (the tunnel limit applies only to active connections). Up to 32 alternative remote stations, each with its own routing tag, can be defined per VPN connection. Automatic selection may be sequential, or dependant on the last connection, or random (VPN load balancing)
Line monitoring	Line monitoring with LCP echo monitoring, dead-peer detection and up to 4 addresses for end-to-end monitoring with ICMP polling

## VPN

IPSec over HTTPS	Enables IPSec VPN based on TCP (at port 443 like HTTPS) which can go through firewalls in networks where e. g. port 500 for IKE is blocked. Suitable for client-to-site connections and site-to-site connections. IPSec over HTTPS is based on the NCP VPN Path Finder technology
Number of VPN tunnels	Max. number of concurrent active IPSec, PPTP (MPPE) and L2TPv2 tunnels: 5 (25 with VPN 25 Option). Unlimited configurable connections. Configuration of all remote sites via one configuration entry when using the RAS user template or Proadaptive VPN.
Hardware accelerator	Integrated hardware accelerator for 3DES/AES encryption and decryption
Realtime clock	Integrated, buffered realtime clock to save the date and time during power failure. Assures timely validation of certificates in any case
Random number generator	Generates real random numbers in hardware, e. g. for improved key generation for certificates immediately after switching-on
1-Click-VPN Client assistant	One click function in LANconfig to create VPN client connections, incl. automatic profile creation for the LANCOM Advanced VPN Client
1-Click-VPN Site-to-Site	Creation of VPN connections between LANCOM routers via drag and drop in LANconfig
IKE, IKEv2	IPSec key exchange with Preshared Key or certificate (RSA signature, ECDSA-Signature, digital signature)
Smart Certificate*	Convenient generation of digital X.509 certificates via an own certification authority (SCEP-CA) on the webpage or via SCEP.
Certificates	X.509 digital multi-level certificate support, compatible with Microsoft Server / Enterprise Server and OpenSSL. Secure Key Storage protects a private key (PKCS#12) from theft.
Certificate rollout	Automatic creation, rollout and renewal of certificates via SCEP (Simple Certificate Enrollment Protocol) per certificate hierarchy
Certificate revocation lists (CRL)	CRL retrieval via HTTP per certificate hierarchy
OCSP Client	Check X.509 certifications by using OCSP (Online Certificate Status Protocol) in real time as an alternative to CRLs

LCOS 10.50

# LANCOM 1781AW

## VPN

OCSP Server/Responder*	Offers validity information for certificates created with Smart Certificate via OCSP
XAUTH	XAUTH client for registering LANCOM routers and access points at XAUTH servers incl. IKE-config mode. XAUTH server enables clients to register via XAUTH at LANCOM routers. Connection of the XAUTH server to RADIUS servers provides the central authentication of VPN-access with user name and password. Authentication of VPN-client access via XAUTH and RADIUS connection additionally by OTP token
RAS user template	Configuration of all VPN client connections in IKE ConfigMode via a single configuration entry
Proadaptive VPN	Automated configuration and dynamic creation of all necessary VPN and routing entries based on a default entry for site-to-site connections.
Algorithms	3DES (168 bit), AES-CBC and -GCM (128, 192 or 256 bit), Blowfish (128 bit), RSA (1024-4096 bit), ECDSA (P-256-, P-384-, P-521-curves), Chacha20-Poly 1305 and CAST (128 bit). OpenSSL implementation with FIPS-140 certified algorithms. MD-5, SHA-1, SHA-256, SHA-384 or SHA-512 hashes
NAT-Traversal	NAT-Traversal (NAT-T) support for VPN over routes without VPN passthrough
LANCOM Dynamic VPN*	Enables VPN connections from or to dynamic IP addresses. The IP address is communicated via ISDN B- or D-channel or with the ICMP or UDP protocol in encrypted form. Dynamic dial-in for remote sites via connection template
Dynamic DNS	Enables the registration of IP addresses with a Dynamic DNS provider in the case that fixed IP addresses are not used for the VPN connection
Specific DNS forwarding	DNS forwarding according to DNS domain, e.g. internal names are translated by proprietary DNS servers in the VPN. External names are translated by Internet DNS servers
Split DNS	Allows the selective forwarding of traffic for IKEv2 depending on the addressed DNS domain.
IPv4 VPN	Connecting private IPv4 networks
IPv4 VPN over IPv6 WAN	Use of IPv4 VPN over IPv6 WAN connections
IPv6 VPN	Connecting private IPv6 networks
IPv6 VPN over IPv4 WAN	Use of IPv6 VPN over IPv4 WAN connections
Radius	RADIUS authorization and accounting, outsourcing of VPN configurations in external RADIUS server in IKEv2, RADIUS CoA (Change of Authorization)
High Scalability VPN (HSVPN)	Transmission of multiple, securely separated networks within a VPN tunnel
Advanced Mesh VPN	On demand dynamic VPN tunnel establishment between branches
IKEv2-EAP*	VPN clients can be authenticated with IKEv2-EAP against a central database like Microsoft Windows Server or RADIUS Server
Two-factor authentication*	Two-factor authentication with LANCOM Advanced VPN Client via IKEv2 EAP-OTP
*)	Only with VPN 25 option



LCOS 10.50

# LANCOM 1781AW

## Performance

**Routing-Performance** Data regarding the overall routing performance can be found inside the LANCOM tech paper "Routing-Performance" on [www.lancom-systems.com](http://www.lancom-systems.com)

## VoIP

**SIP ALG** The SIP ALG (Application Layer Gateway) acts as a proxy for SIP communication. For SIP calls the ALG opens the necessary ports for the corresponding media packets. Automatic address translation (STUN is no longer needed).

## Interfaces

**WAN: ADSL2+** → Compliant to: ADSL2+ as per ITU G.992.5 Annex A/Annex B/Annex J/Annex M with DPBO, ADSL2 as per ITU G.992.3 Annex A/Annex B/Annex J/Annex M, ADSL as per ITU.G.992.1 Annex A/Annex B  
 → Supports one virtual ATM circuit (VPI, VCI pair) at a time  
 → Compliant to: Deutsche Telekom U-R2 (1TR112)

**Ethernet ports** 4 individual 10/100/1000 Mbps Ethernet ports; up to 3 ports can be operated as additional WAN ports with load balancing. Ethernet ports can be electrically disabled within LCOS configuration. The ports support energy saving according to IEEE 802.3az

**Port configuration** Each Ethernet port can be freely configured (LAN, DMZ, WAN, monitor port, off). LAN ports can be operated as a switch or separately. Additionally, external DSL modems or termination routers can be operated as a WAN port with load balancing and policy-based routing. DMZ ports can be operated with their own IP address range without NAT

**USB 2.0 host port** USB 2.0 hi-speed host port for connecting USB printers (USB print server), serial devices (COM port server), USB data storage (FAT file system); bi-directional data exchange is possible

**ISDN** ISDN BRI port (S0 bus)

**Serial interface** Serial configuration interface / COM port (8 pin Mini-DIN): 9,600 - 115,000 baud, suitable for optional connection of analog/GPRS modems. Supports internal COM port server and allows for transparent asynchronous transmission of serial data via TCP

**External antenna connectors** Two reverse SMA connectors

## Management and monitoring

**Management** LANCOM Management Cloud, LANconfig, WEBconfig, WLAN controller, LANCOM Layer 2 management (emergency management)

**Management functions** Alternative boot configuration, voluntary automatic updates for LCMS and LCOS, individual access and function rights up to 16 administrators, RADIUS and RADSEC user management, remote access (WAN or (W)LAN, access rights (read/write) adjustable separately), SSL, SSH, HTTPS, Telnet, TFTP, SNMP, HTTP, access rights via TACACS+, scripting, timed control of all parameters and actions through cron job

**FirmSafe** Two stored firmware versions, incl. test mode for firmware updates

**automatic firmware update** configurable automatic checking and installation of firmware updates

**Monitoring** LANCOM Management Cloud, LANmonitor, WLANmonitor

LCOS 10.50

# LANCOM 1781AW

## Management and monitoring

Monitoring functions	Device SYSLOG, SNMPv1,v2c,v3 incl. SNMP-TRAPS, extensive LOG and TRACE options, PING and TRACEROUTE for checking connections, internal logging buffer for firewall events
Monitoring statistics	Extensive Ethernet, IP and DNS statistics; SYSLOG error counter, accounting information exportable via LANmonitor and SYSLOG
LANCAPI	Available for all LANCOM routers with integrated ISDN interface. LANCAPI provides CAPI 2.0 features for Microsoft Windows to utilize ISDN channels over the IP network
CAPI Faxmodem	Softmodem for Microsoft Windows that makes use of LANCAPI to send and receive faxes via ISDN
IPerf	IPerf is a tool for measurements of the bandwidth on IP networks (integrated client and server)
SLA-Monitor (ICMP)	Performance monitoring of connections
Netflow	Export of information about incoming and outgoing IP traffic
SD-WLAN	SD-WLAN – automatic WLAN configuration via the LANCOM Management Cloud
SD-LAN	SD-LAN – automatic LAN configuration via the LANCOM Management Cloud
SD-WAN	SD-WAN – automatic WAN configuration via the LANCOM Management Cloud
*) Note	Not for use with All-IP connection

## Hardware

Environment	Temperature range 5–40° C; humidity 0–95%; non-condensing
Housing	Robust synthetic housing, rear connectors, ready for wall mounting, Kensington lock; 210 x 45 x 140 mm (W x H x D)
Fans	None; fanless design without rotating parts, high MTBF
Power consumption (max)	12.5 watt

## Declarations of conformity\*

Europe/EFTA	CE
Wi-Fi Alliance Certification	Wi-Fi Certified
IPv6	IPv6 Ready Gold
Country of Origin	Made in Germany
*) Note	You will find all declarations of conformity on our website at <a href="http://www.lancom-systems.com/doc">www.lancom-systems.com/doc</a>

LCOS 10.50

# LANCOM 1781AW

## Scope of delivery

Manual	Hardware Quick Reference (DE/EN), Installation Guide (DE/EN)
Cable	1 Ethernet cable, 3 m
Cable	ADSL cable, 3m
Cable*	ISDN cable, 3m
Antennas	Two 3 dBi external dipole dual-band antennas, one internal 3dBi dipole dual-band antenna
Power supply unit	External power adapter (230 V), NEST 12 V/2.0 A DC/S, coaxial power connector 2.1/5.5 mm, temperature range from -5 to +45° C, LANCOM item no. 111303 (EU)/ External power adapter (230 V), NEST 12 V/1.5 A DC/S, coaxial power connector 2.1/5.5 mm, temperature range from -5 to +45° C, LANCOM item no 110829 (UK)
*) Note	Not available for FCC version.

## Support

Warranty	3 years For details, please refer to the General Warranty Conditions at: <a href="http://www.lancom-systems.com/warranty-conditions">www.lancom-systems.com/warranty-conditions</a>
Software updates	Regular free updates as part of the LANCOM Software Lifecycle Managements ( <a href="http://www.lancom-systems.com/lifecycle">www.lancom-systems.com/lifecycle</a> )
Manufacturer support	Free technical manufacturer support as part of the LANCOM Software Lifecycle Management ( <a href="http://www.lancom-systems.com/lifecycle">www.lancom-systems.com/lifecycle</a> ).

## Software

Software Lifecycle Management	After discontinuation, the device is subject to the LANCOM Software Lifecycle Management. Details can be found at: <a href="http://www.lancom-systems.com/lifecycle">www.lancom-systems.com/lifecycle</a>
Anti-backdoor policy	Products from LANCOM are free of hidden access paths (backdoors) and other undesirable features for introducing, extracting or manipulating data. The trust seal "IT Security made in Germany" (ITSMIG) and certification by the German Federal Office for Information Security (BSI) confirm the trustworthiness and the outstanding level of security.

## Options

VPN	LANCOM VPN-25 Option (25 channels), item no. 60083
LANCOM Content Filter	LANCOM Content Filter +10 user (additive up to 100), 1 year subscription, item no. 61590
LANCOM Content Filter	LANCOM Content Filter +25 user (additive up to 100), 1 year subscription, item no. 61591
LANCOM Content Filter	LANCOM Content Filter +100 user (additive up to 100), 1 year subscription, item no. 61592
LANCOM Content Filter	LANCOM Content Filter +10 user (additive up to 100), 3 year subscription, item no. 61593
LANCOM Content Filter	LANCOM Content Filter +25 user (additive up to 100), 3 year subscription, item no. 61594

LCOS 10.50

# LANCOM 1781AW

## Options

LANCOM Content Filter	LANCOM Content Filter +100 user (additive up to 100), 3 year subscription, item no. 61595
LANcare Basic S	Service package with security updates and support entitlement* until EOL and 5 years replacement service (* support access required, e.g. support contract or LANCOM Service Packs 24/7 or 10/5), item no. 10720
LANcare Advanced S	Service package with security updates and support entitlement* until EOL and 5 years NBD advance replacement (* support access required, e.g. support contract or LANCOM Service Packs 24/7 or 10/5), item no. 10730
LANCOM Public Spot	Hotspot option for LANCOM products, versatile access (via voucher, e-mail, SMS), including a comfortable setup wizard, secure separation of guest access and internal network, item no. 60642
LANCOM All-IP Option	Upgrade option for the operation of the LANCOM routers with All-IP connections, support of PBX systems and telephony devices as well as voice & fax services, incl. Voice Call Manager, All-IP (TAE/RJ45) and cross-over adapters (TE/NT), item no. 61422
Fax Gateway	LANCOM Fax Gateway Option activates 'hardfax' within the router. Supports 2 parallel fax channels with LANCAPI ('fax group 3' without use of CAPI Faxmodem), item no. 61425
LANCOM Public Spot PMS Accounting Plus	Extension of the LANCOM Public Spot (XL) Option for the connection to hotel billing systems with FIAS interface (such as Micros Fidelio) for authentication and billing of guest accesses for 178x/19xx routers, WLCs, and current central-site gateways, item no. 61638
LANCOM VoIP +10 Option	Upgrade for LANCOM VoIP router with 10 additional internal VoIP numbers (additionally up to 40) and 10 external SIP lines (additionally up to 55) item no. 61423

## LANCOM Management Cloud

LANCOM LMC-B-1Y LMC License	LANCOM LMC-B-1Y License (1 Year), enables the management of one category B device for one year via the LANCOM Management Cloud, item no. 50103
LANCOM LMC-B-3Y LMC License	LANCOM LMC-B-3Y License (3 Years), enables the management of one category B device for three years via the LANCOM Management Cloud, item no. 50104
LANCOM LMC-B-5Y LMC License	LANCOM LMC-B-5Y License (5 Years), enables the management of one category B device for five years via the LANCOM Management Cloud, item no. 50105

## Accessories

LANCOM WLAN controllers	LANCOM WLC-30, Art.-Nr. 61789 (EU), LANCOM WLC-1000, Art.-Nr. 61783 (EU), LANCOM WLC Basic Option for Routers, Art.-Nr. 61639
Antenna cable	AirLancer cable NJ-NP 3m, item no. 61230, AirLancer cable NJ-NP 6m, item no. 61231, AirLancer cable NJ-NP 9m, item no. 61232
Antenna cable	AirLancer cable NJ-NP 3m antenna cable extension for connection with LANCOM outdoor antennas, item no. 61230
Antenna cable	AirLancer cable NJ-NP 6m antenna cable extension for connection with LANCOM outdoor antennas, item no. 61231
Antenna cable	AirLancer cable NJ-NP 9m antenna cable extension for connection with LANCOM outdoor antennas, item no. 61232

LCOS 10.50

# LANCOM 1781AW

## Accessories

Surge arrester (antenna cable)	AirLancer SN-ANT surge arrester (2.4 and 5 GHz), to be integrated between Access Point and antenna, item no. 61258
Surge arrester (antenna cable)	AirLancer Extender SA-5L surge arrester (2.4 and 5 GHz), to be integrated between Access Point and antenna, item no. 61553
Surge arrester (LAN cable)	AirLancer Extender SN-LAN surge arrester (LAN cable), item no. 61261
19" Rack Mount	19" rack mount adaptor, item no. 61501
LANCOM Wall Mount	For simple, theft-proof mounting of LANCOM devices with plastic housings, item no. 61349
LANCOM Wall Mount (White)	For simple, theft-proof mounting of LANCOM devices with plastic housings, item no. 61345
LANCOM Serial Adapter Kit	For the connection of V.24 modems with AT command set and serial interface for the connection to the LANCOM COM interface, incl. serial cable and connection plug, item no. 61500
VPN Client Software	LANCOM Advanced VPN Client for Windows 7,8/8.1,10,11 - single license, item no. 61600
VPN Client Software	LANCOM Advanced VPN Client for Windows 7,8/8.1,10,11 - 10 licenses, item no. 61601
VPN Client Software	LANCOM Advanced VPN Client for Windows 7,8/8.1,10,11 - 25 licenses, item no. 61602
VPN Client Software	LANCOM Advanced VPN Client for Mac OS X (10.5 Intel only, 10.6 or higher), single license, item no. 61606
VPN Client Software	LANCOM Advanced VPN Client for Mac OS X (10.5 Intel only, 10.6 or higher), 10 licenses, item no. 61607
*) Note	The polarization diversity antennas require 2 cables and surge arrestors

## Item number(s)

LANCOM 1781AW (EU)	62014
LANCOM 1781AW (UK)	62015
LANCOM 1781AW (US)*	62041

LCOS 10.50

# LANCOM 1781AW

**Item number(s)**

\*) Note There are no ISDN functions available in the US-Version

