

LANCOM GS-3528XUP

Multi-Gigabit Ethernet access switch with PoE++ and up to 90W per port for highest PoE demands



For scenarios that demand data-intensive network components without extensive electrical installations, this 28-port multi-Gigabit access switch with the latest IEEE 802.3bt Power over Ethernet standard is the perfect choice. With 12 of its 24 ports supporting 2.5-Gigabit Ethernet, it provides the high-performance basis necessary for operating Wi-Fi 6E access points and other network components with high-performance requirements, for example. A further 4x SFP+ ports and basic layer-3 features such as static routing and DHCP server make this the expert device for smart management with numerous security features for small and medium-sized networks.

- Multi-Gigabit access switch with 12x 2.5-Gigabit Ethernet ports, 12x 1-Gigabit Ethernet ports, and 4x SFP+
- Basic layer-3 features like static routing and DHCP server
- PoE support as per IEEE 802.3af/at (1G ports) and IEEE 802.3bt Type 4 (2.5G ports) with up to 740 watts
- Security with configurable access control on all ports as per IEEE 802.1X
- Secure remote management through TACACS+, SSH, SSL, and SNMPv3
- Convenient integration into LANCOM monitoring systems
- Cloud-managed LAN – for quick and easy configuration via the LANCOM Management Cloud
- Ideal in combination with newest Wi-Fi 6E access points
- IPv6 and IPv4 support for modern enterprise networks
- 5-year warranty on all components

LANCOM GS-3528XUP

High power output on 28 ports

The LANCOM GS-3528XUP is equipped with 12x 2.5-Gigabit Ethernet ports and 4 SFP+ ports that support transmission rates of up to 10 Gbps. With a data throughput of 164 Gbps on the backplane, it offers full performance even under load. This makes the multi-Gigabit access switch a high-performance basis for modern network infrastructures in any industry or field of application.

A high-performance basis for Wi-Fi 6E

Thanks to 12 high-performance 2.5 Gigabit Ethernet ports including PoE according to IEEE 802.3bt (PoE++), the LANCOM GS-3528XUP is the ideal basis for integrating the new Wi-Fi 6E standard into modern infrastructures. Because Wi-Fi 6E access points like the new LANCOM LX-6500 with 4 streams and 3 bands each mean on the one hand increased performance requirements that exceed simple Gigabit Ethernet, on the other hand for the first time the power consumption of these access points exceeds the threshold of classic PoE+ with 30W.

Centralized power supply without additional electrical installations

The LANCOM GS-3528XUP is a high-performance PoE switch that directly powers PoE devices connected to it: there is no need of additional power supply units or cabling. It supports the Power over Ethernet standards IEEE 802.3at/af (PoE+) and IEEE 802.3bt (PoE++, type 4) with up to 90 watts per port. Thanks to high power reserves with a total output of 740 watts, it is therefore ideal for efficient power supply of end devices with highest energy requirements. In addition to WiFi 6E access points, this also includes end devices such as lighting or touch screens that can be operated via Power over Ethernet for the first time.

Static routing for fast data exchange

The LANCOM GS-3528XUP supports the basic layer-3 feature static routing and thus the shift of certain routing tasks from the router to the switch. Administrator-predefined network routes, through one or multiple network segments, enable fast data transfer especially in scenarios with high data volumes and relieve the router accordingly. Newly available router capacities can then additionally be used to manage external data traffic. As a result, the entire network efficiency is increased.

DHCP server functionality

As a DHCP server, the switch is able to independently and automatically assign IP addresses to clients. The LANCOM GS-3528XUP supports this basic layer-3 function and thus takes over the IP management of the connected network.

Configurable access control

The LANCOM GS-3528XUP excludes rogue clients from gaining unauthorized access to the network. This is ensured by secured access control on all ports as per IEEE 802.1X (port-based, single-based, multi-based, and MAC-based).

LANCOM GS-3528XUP

Secure remote management

Secure communication protocols such as SSH, SSL and SNMPv3 make the LANCOM GS-3528XUP ideal for professional remote network management. The switch also support the TACACS+ protocol for authentication, authorization, and accounting. This optimized solution promises maximum security for multi-site network management and monitoring.

Cloud-managed LAN - days become minutes

The LANCOM GS-3528XUP offers fast and easy network integration and automatic configuration assignment with the LANCOM Management Cloud - without manual configuration. In this way, even complex networking scenarios are easy to administer. Cloud-managed LAN eliminates the need for a single device configuration for holistic network orchestration. In addition, automatic VLAN assignment to the desired switch ports is possible. The configurations can be coordinated with each other across locations and network architectures, and at the same time rolled out or updated at the click of a mouse.

IPv6 and IPv4 support

Thanks to its dual-stack implementation, the LANCOM GS-3528XUP operates in pure IPv4, pure IPv6 or in mixed networks. Applications such as SSL, SSH, Telnet or TFTP can continue to be operated on IPv6 networks. Supported IPv6 features includes stateless auto configuration, neighbor detection, and MLD snooping.

LANCOM GS-3528XUP

Security

Secure Shell Protocol (SSH)	SSH for a secure remote configuration
Secure Sockets Layer (SSL)	SSL to encrypt HTTP connections; advanced security for browser-based configuration via web interface
IEEE 802.1X	IEEE 802.1X access control on all ports; RADIUS for authentication, authorization and accounting with e.g. MD5 hashing; guest VLAN; dynamic VLAN assignment
Private VLAN edge	Layer 2 isolation between clients in the same VLAN ("protected ports"); support multiple uplinks
Port security	Locking of MAC addresses to ports; limiting of the number of learned MAC addresses
IP source guard	Blocking access for illegal IP addresses on specific ports
Access control lists	Drop or rate limitation of connections based on source and destination MAC addresses, VLAN ID, IP address (IPv4/IPv6), protocol, port, DSCP/IP precedence, TCP/UDP source and destination ports, IEEE 802.1p priority, ICMP packets, IGMP packets, TCP flag
RADIUS/TACACS+	Authentication, authorization and accounting of configuration changes by RADIUS or TACACS+
Storm Control	Multicast/Broadcast/Unicast storm suppression
Isolated Group	Allows certain ports to be designated as protected. All other ports are non-isolated. Traffic between isolated group members is blocked. Traffic can only be sent from isolated group to non-isolated group.

Performance

Switching technology	Store and forward with latency less than 4 microseconds
MAC addresses	Support of max 32K MAC addresses
Throughput	Max. 164 Gbps on the backplane
Maximum packet processing	122 million packets per second (mpps) at 64-byte packets
VLAN	Port based and IEEE 802.1q tag based VLAN with up to 4,093 VLAN; Supports ingress and egress packet filter in port based VLAN
Jumbo frame support	Jumbo frame support with up to 10240 bytes

PoE nach IEEE 802.3bt and IEEE 802.3at/af

2.5G Ports	12x IEEE 802.3bt 2.5G PoE ports with up to 90W per port (type 4, compatible to IEEE 802.3at/af powered devices), limited by the maximum PoE power supplied
1G Ports	24x IEEE 802.3at 1G PoE ports (compatible to IEEE 802.3af powered devices), limited by the maximum PoE power supplied
Power	740 W total power with dynamic load balancing on all ports
Priorisation	Supports port based priority and PoE status setting

LANCOM GS-3528XUP

PoE nach IEEE 802.3bt and IEEE 802.3at/af

Status information Monitoring via LED, displaying the actual power consumption per port in web interface

Energy efficiency (Green Ethernet)

Energy detection Energy efficiency according to IEEE 802.3az. Automatically turns off power on Gigabit Ethernet RJ-45 port when detecting link down or Idle of client. Active mode is resumed without loss of any packets when the switch detects the link up

Cable length detection Adjusts the signal strength based on the cable length. Reduces the power consumption for short cable

Layer 3 features

Number of L3 interfaces up to 128

Static routing (IPv4/IPv6) Hardware based static routing (IPv4/IPv6) with a number of 128 possible routes

DHCP Server DHCP Server per VLAN

Layer 2 switching

Spanning Tree Protokoll (STP) / Rapid STP / Multiple STP Standard Spanning Tree according to IEEE 802.1d with fast convergence support of IEEE 802.1w (RSTP); using Multiple Spanning Tree instances by default according to IEEE 802.1s (MSTP)

Link Aggregation Control Protocol (LACP) Support of 26 groups containing up to 4 ports each according to IEEE 802.3ad

VLAN Support for up to 4K VLANs simultaneously (out of 4093 VLAN Ids); matching due to port, IEEE 802.1q tagged VLANs, MAC addresses, IP subnet and Private VLAN Edge function ("protected ports")

Voice VLAN Voice traffic is automatically assigned to a voice-specific VLAN and treated with appropriate levels of QoS

IGMP multicasts IGMP v1, v2, v3 to limit bandwidth-intensive multicast traffic to ports with requesters; supports 1024 multicast groups; source-specific multicasting

IGMP querier Support of multicast domains of snooping switches in the absence of a multicast router

IGMP proxy IGMP proxy to pass IGMP messages through

MLD v1/v2 Multicast Listener Discovery - IPv6 multicast packets are transmitted to interested listeners only

Generic VLAN registration VLAN registration with GVRP according to IEEE 802.1q for automatic delivery of VLANs in bridged domains

DHCP Relay Agent Relay of DHCP broadcast request to different LANs

Supported DHCP options
 → DHCP option 66
 → DHCP option 67
 → DHCP option 82

LANCOM GS-3528XUP

Interfaces

Ethernet	<ul style="list-style-type: none"> → 12 TP ports 100/1000/2500 Mbps → 12 TP ports 10/100/1000 Mbps → 4 SFP+ ports 1/10 Gbps → 28 concurrent Ethernet ports in total
----------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Console port	RJ45 configuration port for command line access
--------------	-------------------------------------------------

Management and monitoring

Management	LANconfig, WEBconfig, LANCOM Management Cloud, Industry Standard CLI
Command Line Interface (CLI)	Configuration and status display from the command line with console application and direct connection to console port, via Telnet or SSH
Monitoring	LANmonitor, LANCOM Management Cloud
Remote Monitoring	Integrated RMON software agent supports 4 RMON groups (history, statistics, alarms and events) for enhanced traffic management, monitoring and analysis
Port Mirroring	Traffic can be mirrored from on port to another for investigation with network analyzer or RMON probe. Up to 27 ports can be mirrored to a single mirror port. Single sessions can be selected
Security	Access rights (read/write) can be set up separately, access control list
SNMP	SNMP management via SNMPv1, v2c or v3 with support of traps. User-based security model for SNMPv3 (USM)
Diagnosis	Diagnosis from the switch with PING and cable diagnosis
Firmware update	<ul style="list-style-type: none"> → Update via WEBconfig and browser (HTTP/HTTPS) → Update via TFTP and LANconfig → Dual firmware image to update during operation
Secure Copy	Securely import and export files
DHCP client	Automatic assignment of the management IP address by DHCP
SNTP	Automatic time settings with Simple Network Time Protocol (SNTP)
s-flow	Standard for monitoring of high-speed-networks. Visualization of network use, accounting an analysis to protect your network against dangers

Hardware

Weight	10.80 lbs (4.9 kg)
Power supply	Internal power supply unit (100 – 240 V, 50 – 60 Hz)
Environment	Temperature range 0 – 40° C; short term temperature conditions 0 – 50°C; humidity 10 – 90%; non-condensing

LANCOM GS-3528XUP

Hardware

Housing	Robust metal housing, 19" 1U (442 x 44 x 375 mm > W x H x D) with removable mounting brackets, network connectors on the front
Fans	1
Power consumption (max)	870 W
Power consumption (idle)	42 W
PoE Budget	740 W
Heat power (max)	444 BTU/h
Acoustic noise (typ)	48 dBa

Software

LCOS version	based on LCOS SX 4.00
Software Lifecycle Management	After discontinuation, the device is subject to the LANCOM Software Lifecycle Management. Details can be found at: www.lancom.de/lifecycle
Anti-backdoor policy	Products from LANCOM are free of hidden access paths (backdoors) and other undesirable features for introducing, extracting or manipulating data. The trust seal "IT Security made in Germany" (ITSMIG) and certification by the German Federal Office for Information Security (BSI) confirm the trustworthiness and the outstanding level of security

Declarations of conformity*

Europe/EFTA	CE
North America	FCC/IC
Australia / New Zealand	ACMA
*) Note	The full text of the specific Declaration of Conformity is available at the following Internet address: www.lancom-systems.com/doc

Supported IEEE standards

IEEE 802.1AB	Link Layer Discovery Protocol (LLDP)
IEEE 802.1AB	LLDP-MED
IEEE 802.1ad	Q-in-Q tagging
IEEE 802.1ak	MRP and MVRP - Multiple Registration Protocol and Multiple VLAN Registration Protocol
IEEE 802.1d	MAC Bridging
IEEE 802.1d	Spanning Tree

LANCOM GS-3528XUP

Supported IEEE standards

IEEE 802.1p	Class of Service
IEEE 802.1q	VLAN
IEEE 802.1s	Multiple Spanning Tree Protocol (MSTP)
IEEE 802.1w	Rapid Spanning Tree Protocol (RSTP)
IEEE 802.1X	Port Based Network Access Control
IEEE 802.3	10Base-T Ethernet
IEEE 802.3ab	1000Base-TX Ethernet
IEEE 802.3ad	Link Aggregation Control Protocol (LACP)
IEEE 802.3ae	10 Gigabit Ethernet over fiber
IEEE 802.3af	Power over Ethernet (PoE)
IEEE 802.3at	Power over Ethernet Plus (PoE+)
IEEE 802.3bt	Power over Ethernet++ (PoE++) Type 4
IEEE 802.3az	Energy Efficient Ethernet
IEEE 802.3bz	2.5GBASE-T Ethernet
IEEE 802.3u	100Base-T Ethernet
IEEE 802.3x	Flow Control
IEEE 802.3z	1000Base-X Ethernet

Supported RFC standards

RFC 854	Telnet Protocol Specification
RFC 1213	MIB II
RFC 1215	SNMP Generic Traps
RFC 1493	Bridge MIB
RFC 1769	Simple Network Time Protocol (SNTP)
RFC 2021	Remote Network Monitoring MIB v2 (RMONv2)
RFC 2233	Interface MIB

LANCOM GS-3528XUP

Supported RFC standards

RFC 2460	Internet Protocol Version 6 (IPv6)
RFC 2613	SMON MIB
RFC 2617	HTTP Authentication
RFC 2665	Ethernet-Like MIB
RFC 2674	IEEE 802.1p and IEEE 802.1q Bridge MIB
RFC 2818	Hypertext Transfer Protocol Secure (HTTPS)
RFC 2819	Remote Network Monitoring MIB (RMON)
RFC 2863	Interface Group MIB using SMIv2
RFC 2933	IGMP MIB
RFC 3019	MLDv1 MIB
RFC 3414	User based Security Model for SNMPv3
RFC 3415	View based Access Control Model for SNMP
RFC 3587	IPv6 Global Unicast Address Format
RFC 3621	Power Ethernet MIB
RFC 3635	Ethernet-Like MIB
RFC 3636	IEEE 802.3 MAU MIB
RFC 4133	Entity MIBv3
RFC 4188	Bridge MIB
RFC 4251	The Secure Shell Protocol Architecture (SSH)
RFC 4291	IP Version 6 Addressing Architecture
RFC 4443	Internet Control Message Protocol (ICMPv6)
RFC 4668	RADIUS Authentication Client MIB
RFC 4670	RADIUS Accounting MIB
RFC 5519	Multicast Group Membership Discovery MIB
RFC 7513	DHCP Snooping

LANCOM GS-3528XUP

Supported RFC standards

RFC 5519	IGMP- and MLD-Snooping
----------	------------------------

Scope of delivery

Manual	Hardware Quick Reference (DE/EN), Installation Guide (DE/EN)
--------	--------------------------------------------------------------

Cable	Serial configuration cable, 1.5m
-------	----------------------------------

Cable	IEC power cord
-------	----------------

19" brackets	Two 19" brackets for rackmounting
--------------	-----------------------------------

Support

Warranty	5 years, for details, please refer to the General Warranty Conditions at: www.lancom-systems.com/warranty-conditions
----------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

LANCOM support	Free technical manufacturer support as part of the LANCOM Software Lifecycle Management www.lancom.de/lifecycle
----------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------

LANcare Advanced M	Service package with security updates and support entitlement* until EOL and 5 years NBD advance replacement (* support access required, e.g. support contract or LANCOM Service Packs 24/7 or 10/5), item no. 10731
--------------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

LANCOM Management Cloud

LANCOM LMC-B-1Y LMC License	LANCOM LMC-B-1Y License (1 Year), enables the management of one category B device for one year via the LANCOM Management Cloud, item no. 50103
-----------------------------	------------------------------------------------------------------------------------------------------------------------------------------------

LANCOM LMC-B-3Y LMC License	LANCOM LMC-B-3Y License (3 Years), enables the management of one category B device for three years via the LANCOM Management Cloud, item no. 50104
-----------------------------	----------------------------------------------------------------------------------------------------------------------------------------------------

LANCOM LMC-B-5Y LMC License	LANCOM LMC-B-5Y License (5 Years), enables the management of one category B device for five years via the LANCOM Management Cloud, item no. 50105
-----------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------

LANCOM LMC-B-10Y LMC License	LANCOM LMC-B-5Y License (10 Years), enables the management of one category B device for ten years via the LANCOM Management Cloud, item no. 50133
------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------

Accessories*

1000Base-SX SFP module	LANCOM SFP-SX-LC1, item no. 61556
------------------------	-----------------------------------

1000Base-LX SFP module	LANCOM SFP-LX-LC1, item no. 61557
------------------------	-----------------------------------

10GBase-SX SFP module	LANCOM SFP-SX-LC10, item no. 61485
-----------------------	------------------------------------

10GBase-LX SFP module	LANCOM SFP-LX-LC10, item no. 61497
-----------------------	------------------------------------

10G multi gigabit Ethernet copper module	LANCOM SFP-CO10-MG, Art.-Nr.: 60170
------------------------------------------	-------------------------------------

10G Direct Attach Cable 1m	LANCOM SFP-DAC10-1m, Art.-Nr.: 61495
----------------------------	--------------------------------------

LANCOM GS-3528XUP

Accessories*

10G Direct Attach Cable 3m LANCOM SFP-DAC10-3m, Art.-Nr.: 60175

LANCOM Power Cord (UK) IEC power cord, UK plug, item no. 61650

LANCOM Power Cord (CH) IEC power cord, CH plug, item no. 61652

LANCOM Power Cord (US) IEC power cord, US plug, item no. 61651

LANCOM Power Cord (AU) IEC power cord, AU plug, item no. 61653

*) Note Support for third-party accessories (SFP and DAC) is excluded and cannot be granted

Item number(s)

LANCOM GS-3528XUP 61476

